



- NOTES:
1. GATE TO BE SET BACK TO ACCOMMODATE EMERGENCY VEHICLE ACCESS (4500mm CLEAR OPENING AT GATE OR USE OF DOUBLE GATES).
 2. PIPE SHALL BE SCHEDULE 40 STEEL UNLESS NOTED TO BE XXS STEEL PIPE.
 3. ALL METAL TO BE PAINTED WITH ONE SHOP COAT OF ZINC CHROMATE PRIMER, AND TWO COATS OF ALKYD GLOSS ENAMEL (YELLOW). PLACE 2000x50 STRIP OF 3M DIAMOND GRADE DG3 FLORESCENT YELLOW 4081 REFLECTIVE TAPE CENTRED ON EACH SIDE OF TOP RAIL.
 4. HEIGHT TO BE 1000 TO 1250 MEASURED TO TOP OF GATE RAIL AT CENTRELINE OF ROAD.
 5. REFER TO CONTRACT DRAWINGS AND SECTION 03 30 53 FOR DETAILED SPECIFICATIONS.

NOT TO SCALE

No.	DATE	REVISION DESCRIPTION	BY	APP
3	APR2022	REVIEWED AND UPDATED 2022	IP	JDh
2	JAN2019	REVIEWED AND UPDATED 2019	DAR	JDh

ACCESS GATE



DWG. No. REV.

SC17 3