



JUMBO: LENGTH – 200mm  
 WIDTH – 100mm  
 AREA – 50 STONES/m<sup>2</sup>  
 THICKNESS – 80mm

**BRICK NOTES:**

1. BOULEVARD BRICKS TO BE "OLD COUNTRY STONE" TYPES 1, 2 & 3, AS AVAILABLE FROM ABBOTSFORD CONCRETE PRODUCTS (OR EQUIVALENT).

- TYPE 1: LENGTH – 226mm  
 WIDTH – 181mm  
 AREA – 25 STONES/m<sup>2</sup>  
 THICKNESS – 60mm
- TYPE 2: LENGTH – 151mm  
 WIDTH – 181mm  
 AREA – 37 STONES/m<sup>2</sup>  
 THICKNESS – 60mm
- TYPE 3: LENGTH – 76mm  
 WIDTH – 181mm  
 AREA – 74 STONES/m<sup>2</sup>  
 THICKNESS – 60mm

BRICK ACCENT BAND TO BE "CHARCOAL" TYPE 2

BRICK FIELD PAVING TO BE 70% "DESERT SAND" AND 30% "TAUPE" TYPES 1, 2 & 3 RANDOM PATTERN.

2. CROSS WALK BRICKS TO BE "HOLLAND" "DESERT BUFF" AS AVAILABLE FROM EXPOCRETE CONCRETE PRODUCTS (OR EQUIVALENT) IN 90° HERRINGBONE PATTERN.

- 3. DRIVEWAY CROSSING BRICKS TO BE "HOLLAND" "CHARCOAL" AS AVAILABLE FROM EXPOCRETE CONCRETE PRODUCTS (OR EQUIVALENT) IN 90° HERRINGBONE PATTERN.
- 4. BRICKS TO BE CONTAINED BY ALUMINUM/STEEL/PLASTIC "L" SHAPED EDGER WHEN NOT ADJACENT TO CONCRETE STRUCTURE.(PERMALOC ALUMINUM STRUCTURE EDGE, EDGE PRO PLASTIC OR APPROVED EQUIVALENT)
- 5. REFER TO MMCD UNIT PAVING SPECIFICATIONS OR AMENDMENTS FOR LEVELING BED, TECHNISEAL POLYMERIC JOINTING SAND, AND OTHER REQUIREMENTS.
- 6. CITY OF KAMLOOPS PARKS DEPARTMENT TO DETERMINE TREEWELL, GRATE AND SILVA CELL REQUIREMENTS & SPECIFICATIONS.
- 7. ALL JUNCTION BOXES AND STRUCTURES TO BE PLACED WITH CONSIDERATION FOR BRICK AND CONCRETE OFFSETS AND ORIENTATION.
- 8. 3m X 3m MOCKUP OF PAVING PATTERN TO BE PROVIDED FOR CITY'S REVIEW AND APPROVAL

NOT TO SCALE

No.	DATE	REVISION DESCRIPTION	BY	APP
2	APR2022	REVIEWED AND UPDATED	IP	JDh
1	OCT2020	FOR REVIEW	JBB	JDh

**DECORATIVE BRICK**



Canada's Tournament Capital

DWG. No. SC-19  
 REV. 2