



DRILL 18Ø HOLE FOR WIREWAY.
COAT HOLE WITH COLD GALVANIZING COMPOUND

SAFETY CABLE (WRAP AROUND
ARM AND ATTACH SNAP HOOK

STANDARD U-BOLT FOR
SPRING CUSHION HANGER
HAS 145mm I.D.

SPRING CUSION MID HANGER
SHOWN. WHEN MOUNTING ON
THE END OF A TYPE 3 ARM
USE END HANGER.


PLUMB

POLE ARM


SPRING CUSHION MID HANGER
OR ALTERNATE ATTACHMENT
SUPPLIED WITH SIGN.

INTERNALLY ILLUMINATED
PEDESTRIAN CROSSWALK SIGN

300mm SIGNAL HEAD WITH
YELLOW LED.
BACK TO BACK INSTALLATION
(REQUIRED BOTH SIDES)



DOWNLIGHT



LOCATION AS NOTED ON
CONTRACT DRAWINGS

CROSSING SIGNAGE AS NOTED
ON CONTRACT DRAWINGS

PEDESTRIAN
PUSH BOTTON

300mm SIGNAL HEAD WITH
YELLOW LED.
BACK TO BACK INSTALLATION.

SIGNAL POLE

NOTES:

1. REFER TO CONTRACT DRAWING,
SECTION 34 41 13 FOR DETAILED
SPECIFICATIONS.

ELEVATION

**INTERNALLY ILLUMINATED
PEDESTRIAN CROSSWALK
SIGN**

CITY OF KAMLOOPS

NO.	DATE	REVISION	DESCRIPTION	BY	APP

DWN. BY: DAR

CHK'D BY: P.Pouliotte

SCALE: N.T.S.

DATE: 11/01/05

DWG. NO.: **SE5.15** REV.: